



LISTED 53Z2

Model # 2P20GR

## Cat # 20FR Female Panel Mount

- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO <u>CONDUCTIVE</u>

PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB. TORQUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS

-SEE REVERSE SIDE FOR DEVICE DIMENSIONS



LISTED

53Z2

ONNECTOR

Model # 2P20GR

## Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2 020, 16 GAUGE, 060 MATERIAL
- PLISH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION TWO METHODS OF WIRE ERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS, INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TORQUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS

\_SEÉ REVERSE SIDE FOR DEVICE DIMENSIONS





LISTED

53Z2

Model # 2P20GR

## Cat # 20FR Female Panel Mount

PANEL CUTOUT 760 X 2 020, 16 GAUGE, .060 MATERIAL

PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

WIRE TERMINATION - TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS

- SLIP WIRE SHOE (PROVIDED) OVER STRANDS, INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TORQUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS SEE REVERSE SIDE FOR DEVICE DIMENSIONS

PANEL CUTOUT .760 X 2.020, 16 GAUGE, .060 MATERIAL

PANEL CUTOUT .760 X 2 020, 16 GAUGE, .060 MATERIAL

CONNECTOR

Model # 2P20GR

PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS

Cat # 20FR Female Panel Mount

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS INSERT THROUGH CROSS HOLE & TERMINATE WITH
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS

-SEE REVERSE SIDE FOR DEVICE DIMENSIONS

## CONNECTOR



LISTED

LISTED

 $53Z_{2}$ 

53Z2

Model # 2P20GR

## Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS TORQUE

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL

- WIRE TERMINATION TWO METHODS OF WIRE ERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS.
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS, INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TORQUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS

SEE REVERSE SIDE FOR DEVICE DIMENSIONS

## CONNECTOR



LISTED

53Z2

## Model # 2P20GR

## Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS, INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TORQUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS

SEE REVERSE SIDE FOR DEVICE DIMENSIONS

## ONNECTOR



LISTED 53Z2

Model # 2P20GR

## Cat # 20FR Female Panel Mount

- PANEL CUTOUT .760 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS TORQUE.

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO <u>CONDUCTIVE</u>

<u>PANEL</u>. MOUNTING STRAP PROVIDES CONDUCTIVE
PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS. INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TOROUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS
- -SEE REVERSE SIDE FOR DEVICE DIMENSIONS

# CONNECTOR



LISTED  $53Z_{2}$ 

Model # 2P20GR

## Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2.020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS

GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO CONDUCTIVE
PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS. INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TORQUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS

SEE REVERSE SIDE FOR DEVICE DIMENSIONS

## CONNECTOR



LISTED 53Z2


Model # 2P20GR

## Cat # 20FR Female Panel Mount

- PANEL CUTOUT 760 X 2 020, 16 GAUGE, 060 MATERIAL
- PUSH DEVICE REARWARD THROUGH CUTOUT AND TIGHTEN MOUNTING SCREW TO 7 IN/LBS TORQUE


GROUNDING TERMINAL NEED NOT BE WIRED SEPERATELY WHEN MOUNTED TO <u>CONDUCTIVE</u> PANEL. MOUNTING STRAP PROVIDES CONDUCTIVE PATH BETWEEN GROUNDING TERMINAL AND PANEL.

- WIRE TERMINATION TWO METHODS OF WIRE TERMINATION ARE OFFERED FOR THE BATES PANEL MOUNTS
- SLIP WIRE SHOE (PROVIDED) OVER STRANDS, INSERT THROUGH CROSS HOLE & TERMINATE WITH 12 IN/LB TORQUE
- #8 RING TERMINAL MAY BE CRIMPED ONTO WIRE & ATTACHED WITH TERMINAL SCREW AT 12 IN/LBS SEE REVERSE SIDE FOR DEVICE DIMENSIONS




Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com


470106



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106


## DIMENSIONS IN INCHES.



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106


## DIMENSIONS IN INCHES.



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106


## DIMENSIONS IN INCHES.



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106


## DIMENSIONS IN INCHES.



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106


## DIMENSIONS IN INCHES.



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

9-2079 o.com 470106

## DIMENSIONS IN INCHES.



Marinco 707 / 226-8600 FAX 707 / 259-2079 www.marinco.com

470106